

Catalogue number: **EUR**□□□-□□ □□□V

Eureka Installation Contactor 24 & 240 VAC



Eureka Installation Contactors



- Current Rating: 25A, 40A, 63A
- Coil Voltage: 24VAC, 240VAC
- 1, 2 and 4 Pole
- AC1 and AC3 rated
- Din rail mounted
- Rigid Construction
- Choice of main contact configurations
- Ideal for mounting in Load Centres and Distribution Boards.

Rated Current		No. of Contacts		Coil Voltage	
225	25 A	11	1N0, 1NC	24	24VAC
425	25 A	02	2NO	240	240VAC
440	40 A	13	1N0, 3NC		
463	63 A	31	3N0, 1NC		
		40	4N0		
		04	4NC		
		22	2N0, 2NC		

Properties

Properties	EUR225	EUR425	EUR440	EUR463
Manufacturer	Eureka			
Product Range	Eureka Installation Contactors			
Current Rating AC1	25 A	25 A	40 A	63 A
Current Rating AC3	9 A	9 A	27 A	30 A
Rated Operational Voltage U_i	240 / 400 V			
Rated Insulation Voltage U_e	500 V			
Standard Compliances	IEC/EN 61095, IEC/EN 60947-4-1			

Dimensions of EUR225

